

AAD-OUT2-F16

2-Channel Analog & Digital Audio Output Card



AAD-OUT2-F16 is a two-channel analog and digital output card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The AAD-OUT2-F16 outputs two analog and digital signals from the chassis

FEATURES

Balanced Analog Audio over Terminal Block Connector S/PDIF Digital Audio over RCA Connector



TECHNICAL SPECIFICATIONS

PORTS: 2 S/PDIF (digital audio) on RCA connectors, 2 balanced audio stereo (analog

audio) on 5-pin terminal blocks

TOTAL BANDWIDTH: Analog (-3db): >100kHz, Digital: 32kHz - 192kHz sample frequency

POWER 5.8W

CONSUMPTION:

OPERATING 0° to +40°C (32° to 104°F)

TEMPERATURE:

STORAGE -40° to $+70^{\circ}$ C (-40° to 158° F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

SAFETY CE

REGULATORY COMPLIANCE:

ENVIRONMENTAL

REGULATORY COMPLIANCE:

Complies with appropriate requirements of RoHs and WEEE

Product Dimensions $19.00 \text{cm} \times 13.00 \text{cm} \times 2.00 \text{cm} (7.48 \text{"} \times 5.12 \text{"} \times 0.79 \text{"}) \text{ W, D, H}$

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

Shipping Weight 0.3kg (0.6lbs) approx