



KRAMER

BC-3X2T7S

14 Conductor Presentation/VGA Bulk Cable

| VGA/UXGA - 15-pin HD



Kramer's BC-3X2T7S is a high-resolution multi-conductor containing 3 mini coaxes, 2 shielded pairs, and 7 single strands. It is the most common type of cable used for construction of 15-pin HD (VGA/UXGA) cables

FEATURES

Quality Construction - Each coax has a 26AWG center conductor and dual shield design consisting of copper braid and aluminum Mylar foil. Rugged and flexible jacket with internal rip cord and sequential markings every meter. Coax dielectrics are color-coded red, green, blue

High Resolution - Supports higher resolution and longer distances than 28AWG versions

Length - Available in reels of 100m (328ft)



TECHNICAL SPECIFICATIONS

COAX	<p>Conductor: 26AWG 7/34 tinned copper</p> <p>Dielectric: Foam polyethylene with red, green, blue color coding</p> <p>Shield: (A) 90% spiral 38AWG tinned copper. (B) Aluminum Mylar foil 25% overlap rate</p> <p>Inner Jacket: PVC</p> <p>Jacket Colors: Black</p>
DIAMETERS	<p>Center Conductor: 0.48mm (0.019in)</p> <p>Dielectric: 1.95mm (0.076in)</p> <p>Individual Coax: 2.6mm (0.102in)</p>
ELECTRICAL	<p>Impedance: 75Ω</p> <p>DC Resistance: 148Ω/km (45Ω/1000ft)</p> <p>Capacitance: 57pF/m (17.3pF/ft)</p> <p>Temperature: -4° to 167°F (-20° to 75°C)</p> <p>Attenuation (dB/30m (100ft)): -0.5dB @1MHz -1.3dB @5MHz -1.9dB @10MHz -4.0dB @50MHz -5.7dB @100MHz -8.0dB @180MHz -14.0dB @400MHz</p>
SHIELDED PAIR	<p>Conductors: 26AWG 7/34 tinned copper</p> <p>Jacket: HD-polyethylene</p> <p>Diameter: 0.34in (0.88mm)</p> <p>Shield: (A) 85% spiral 36AWG tinned copper. (B) Aluminum Mylar foil 25% overlap rate</p> <p>Jacket Colors: White, white/black, red, red/black</p>
SINGLE STRAND	<p>Conductor: 26AWG 7/34 tinned copper</p> <p>Jacket: HD polyethylene</p> <p>Diameter: 0.88mm (0.34in)</p> <p>Jacket Colors: Red, orange, brown, yellow, black, red/black</p>
OVERALL	<p>Shield: (A) 85% spiral 36AWG tinned copper. (B) Aluminum Mylar foil 25% overlap rate</p> <p>Outer Jacket: PVC</p> <p>Outer Jacket Color: Dark gray with white lettering</p> <p>Outer Diameter: 10.0mm (0.393in)</p>
REGULATORY	<p>UL: CL2</p> <p>CSA: C(UL) FT4</p> <p>RoHS: In compliance with European directive 2002/95/IEC</p>



KRAMER

CONFIGURATIONS

BC-3X2T7S-100M	14 Conductor VGA (26 AWG) Bulk Presentation Cable
----------------	---
