

Kramer KronoMeet

Cloud-Based Room Scheduling and Meeting Management Platform



FEATURES

Enterprise Class Comprehensive Room Scheduling, and Management - Empower your staff and guests with intuitive room scheduling, live on-site and remote notifications, and easy meeting search for employees and guests. Kramer KronoMeet is fully integrated with widely used scheduling platforms, including Google Calendar, Microsoft Office 365, and Microsoft Exchange

Fully Customizable and Scalable - Kramer KronoMeet is scalable to your needs, from a small business with a few meeting rooms to a large corporation

On-Screen Information Inside the Meeting Room - Integration with VIA collaboration devices enables automatic reminders on the main display when the meeting is nearly over and another meeting will be starting

Convenient Scheduling Displays - Display meeting schedules on Kramer KronoMeet touch panels at the entrance to each room

Superior User Experience - IPS 1280x800 hi–resolution screen with ±80° horizontal and vertical wide viewing angles, built–in lighting sensor for auto–adaptable brightness, with advanced 10 multi–touch points and 2–finger gesture capabilities

Secured Operation - Highly secured operation of applications such as password protected exit, hidden control buttons and so on

Secured Deployment - Flexible locking options to prevent unwanted panel-mount removal, elegantly designed to remain out of site



TECHNICAL SPECIFICATIONS

KT-107SC

PORTS

1 1000/100/10BaseT Ethernet: On an RJ-45 connector

1 DC power supply: On a 2-pin terminal block

1 USB: On a micro USB 2.0 connector (tabletop mount only)

GENERAL

CPU Performance: 1.6GHz Quad Core, GPU, 2GB RAM, 16GB flash

OS Software: Android 6.0.1

Multi Touch: 10 points, 2-finger gesture

Display: 7" IPS, 1280x800 RGB pixels, 16:10 aspect ratio, ±85° horizontal/vertical

viewing angles, 400cd/m2 brightness, 800:1 contrast ratio

Ethernet Port: 10/100/1000Mbps PoE LAN

Wireless Communication: Wi-Fi 802.11 b/g/n/ac, Bluetooth 4.0

AUDIO

Speakers: 2x1W, 8Ω

Microphone: -42dB ±3dB @1kHz sensitivity

VIDEO

Decoding Format: HEVC/H.265, H.264, H.263, MPEG-1/2/4, VC-1, VP6/8,

RV8/9/10, AVS, MVC, Sorenson Spark, M-JPEG Encoding Format: H.264, MVC, VP8, M-JPEG

Camera: Front, 2M pixels, HD 720p

POWER

Battery: Rechargeable, supports up to 3 hours of Wi-Fi operation

Power over Ethernet: Complies with IEEE802.3af and IEEE802.3at PoE standards

Consumption: 5V DC, 3A

USER INTERFACE

Controls: Hidden Reset, power (ON/OFF), volume buttons

Indicators: Touch panel status LED: flashes green during charging, steady green

for fully charged, red for camera on

PHYSICAL

Case: Black body and cover

Mounting Options: Table top (with docking station), on-wall (with mount unit and

panel mount plate)

ACCESSORIES

Included: Power supply unit adapter (5V, 4.0A AC/DC), tabletop mount, on-wall mount unit, panel-mount plate, right-angle OTG USB cable, installation screws

MEASUREMENTS

Product Dimension: 17.80cm x 13.00cm x 1.30cm (7.01" x 5.12" x 0.51") W, D, H

Product Weight: 0.4kg (0.9lbs) approx.

Shipping Dimension: 35.00cm x 21.00cm x 7.00cm (13.78" x 8.27" x 2.76") W, D,

Н

Shipping Weight: 1.2kg (2.5lbs) approx

KT-1010SC

PORTS

1 Ethernet: On an RJ-45 connector

1 SD card: On an SD card (SDHC Class10 compatible) slot

1 USB: On a USB 2.0 type A connector 1 USB: On a micro USB 2.0 connector

1 Headphone: On a 3.5mm mini jack connector

GENERAL

CPU Performance: GCortex-A17, quad core, up to 1.8 GHz GCPU: Mali-T764, with TE, ASTC, AFBC technology

System Memory: 2GB DDR3 SDRAM Internal Storage Memory: 8GB eMMC

External Storage Memory: SD card (SDHC Class10 compatible)

Touch Panel Type: 10 point capacitive multi-touch type

Wireless Communication: IEEE 802.11 a/b/g/n/ac, Bluetooth: BT4.2

Ethernet: 10/100/1000 Mbps LAN

AUDIO

Speaker unit: 2W+2W

VIDEO

Supported Formats: MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP,

MP4, WMV

Camera: 2M pixels (optional)

Supported Formats: MP2, WMA, WAV, AAC, OGG, ASF

POWER

Source: 12V/2A DC adapter

POE: Power over Ethernet (optional)

USER INTERFACE

Controls: Volume, menu, and power buttons Indicators: LED sidebars to indicate room status

PHYSICAL

Display: TFT LCD, 10.1" (16:9 diagonal), 1280 RGB (H) x 800(V) pixels

Back-light: LED Side-light type

VESA Mounting Ready: Metal-fittings mounting screw holes for 75x75mm VESA

mount

INCLUDED ACCESSORIES

12V AC/DC power adapter, on-wall mounting bracket, installation screws, 2 LED

side bars, panel mounting bracket

MEASUREMENTS

Product Dimension: 25.21cm x 18.00cm x 3.00cm (9.93" x 7.09" x 1.18") W, D, H

Product Weight: 0.6kg (1.3lbs) approx.

Shipping Dimension: 49.70cm x 20.50cm x 5.20cm (19.57" x 8.07" x 2.05") W, D,

Н

Shipping Weight: 1.6kg (3.4lbs) approx

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -10° to +55°C (14° to 131°F)

Humidity: 10% to 90%, RHL non-condensing



CONFIGURATIONS

KT-107SC	7-Inch, wall mount, dedicated touch panel for Kramer KronoMeet – application with 1 year license pre-installed
KRONOMEET-SW- EXT-1Y	Kramer KronoMeet cloud based application - 1 year license
KRONOMEET-SW- EXT-2Y	Kramer KronoMeet cloud based application - 2 year license
KRONOMEET-SW- EXT-4Y	Kramer KronoMeet cloud based application - 4 year license