## **BookIT® Room Scheduling Solution**

Elegant, cost-effective system directly integrated with MS Exchange™ and Google™ G Suite

This elegant, cost-effective and easy-to-deploy system is designed for scheduling any conference room on a network from a BooklT touch panel located outside a meeting room, your mobile device or computer. Its sleek design fits into any décor and the intuitive interface requires little to no user training. BooklT directly integrates with MS Exchange™, Office 365™ and G Suite™, so no additional server or middleware is needed, simplifying implementation and significantly reducing cost.

System Includes: 7" BookIT PoE touch panel device, a wall mounting system (bracket included), BookIT Room Scheduling Software and power adapter (when PoE is unavailable).

For more detailed information, visit www.bookit.tech









## **At-A-Glance Room Scheduling**

Simply identify room status with universal color coding. No need to guess what is happening behind that closed door!







**PENDING** 



OCCUPIED



**ADMIN SETTINGS** 

## **BookIT:** Application Features

- Meeting Room Calendar Color-coded room status of red, gold and green lets you immediately know the availability of a room. Click on the calendar button to see a list of meetings in the room the sign is assigned to. The list is scrollable so you can see out to the end of the booking period allowed in Exchange or Google.
- Schedule Meetings Select "Add", enter your credentials and you can now schedule a meeting in any available room at any available time.
- Meeting Check-In If nobody checks into the room within the configured amount of time, the room will automatically release for others to use. This feature can be enabled, disabled or configured at any time by the administrator.
- **Release Meeting** Your meeting's over early? Make the room available for others by simply releasing the room on the BookIT touch panel display. The end to your meeting will automatically be updated for others to see. Only meetings in session can be released from the BookIT display.
- Extend Meeting Extend the meeting on the BookIT touch panel display. You can extend the meeting for as long as you need based on the room's availability. Only meetings in session can be extended from the BookIT display.
- **Delete Meeting** It's easy to delete a meeting from your phone, computer or at the BookIT display. Only the meeting organizer can delete a meeting. Only meetings in session can be deleted from the BookIT display.
- GUI Options Easily replace the BookIT logo with your own logo. Also choose from different background options.
- **Support** Have a technical issue with a projector or a display? Just touch "Support" and send a predefined message to summon your internal technical support team to the room.
- Multiple Languages Available

## **BookIT:** Admin Features

- Step-by-step setup for Exchange and G Suite
- Set master password for Admin Settings access
- Enable and disable meeting warnings
- Adjust and turn off auto release time
- Control ability to book a meeting from the sign
- Change BookIT logo on display to your own logo
- Change background theme
- Configure content and addresses for technical support

Part #	Description
втх-воокіто7	BookIT Display and Application (includes 1 year of software maintenance)
ВТХ-ВООКІТО7А	BookIT Display and Application (International) (includes 1 year of software maintenance)
BTX-BOOKIT1HW	BookIT 1 Year Extended Hardware Warranty
BTX-BOOKIT1YR	BookIT 1-Year Extended Software Maintenance
BTX-BOOKIT2YR	BookIT 2-Year Extended Software Maintenance
BTX-BOOKITRMB	BookIT Recess Mount Bracket (set)
BTX-BOOKITWM	BookIT Switch Box Mount
BTX-BOOKITMM	BookIT Mullion Mount

2 year hardware warranty included along with 1 year of software maintenance.





		BTX-BOOKIT07	BTX-BOOKIT07A (International)
	Solution	Allwinner A31s, Quad-Core Cortex™- A7 CPU	Allwinner A83T Octa-Core Cortex <sup>™</sup> - A7 CPU
	Display	7in IPS Display, Resolution:1024 x 600, Brightness: 350 cd/m2	
	RAM	1GB	2GB
Handwara Chass	Nand Flash	80	GB
Hardware Specs	Dimensions	7.2in (l) x 4.8in (h) x 1in (d) - (182	mm (I) x 121mm (h) x 25mm (d))
	Operating Temperature	0°C to	50°C
	Storage Temperature -30°C to 80°C		o 80°C
	Certification	FCC	FCC, CE, RoHS
	System	Google Android 4.4.2	Google Android 4.4.4
Android Softwar Features	Video	H.264 2160p video decoding, Multi-format FHD video decoding, including Mpeg1/2, Mpeg4 SP/ASP GMC, H.263, H.264, VP6/8, AVS jizun, Jpeg/Mjpeg,etc., H.264 High Profile 1080p@30fps or 720@60fps encoding, 3840 x 1080@30fp, 3D decoding, BD/SBS/TAB/FP supported complies with RTSP, HTTP, HLS, RTMP, MMS streaming media protocols	
	Audio	Two Speakers 2 X 1 Watt (Integrated 3W Amplifier For External Speakers)	
	Language	Supports multiple languages	
		HDMI Out	
		DC IN Power Terminal (9V-36V)	
Intenfere	Dogle	DC IN Power Tel	rminal (9V-36V)
Interfaces	Back	DC IN Power Te	· (· · · · · /
Interfaces	Back		ice (RJ45) - PoE
	Back WiFi + Bluetooth	Ethernet Interfa	ice (RJ45) - PoE Mode By Default
Interfaces		Ethernet Interfa  USB Socket HOST	ice (RJ45) - PoE  Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0
	WiFi + Bluetooth LAN Port	Ethernet Interfa USB Socket HOST WiFi (802.11b/g/n), Bluetooth V2.1 Etherne	Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0
	WiFi + Bluetooth LAN Port Input Voltage	Ethernet Interfa USB Socket HOST WiFi (802.11b/g/n), Bluetooth V2.1 Etherne	ice (RJ45) - PoE  Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0  et RJ45  C - 50/60Hz
Network	WiFi + Bluetooth  LAN Port  Input Voltage  Rated Voltage	Ethernet Interfa  USB Socket HOST  WiFi (802.11b/g/n), Bluetooth V2.1  Ethernet  100-240VAG	Acce (RJ45) - PoE  Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0  et RJ45  C - 50/60Hz
	WiFi + Bluetooth LAN Port Input Voltage	Ethernet Interfa USB Socket HOST WiFi (802.11b/g/n), Bluetooth V2.1 Etherne	Acce (RJ45) - PoE  Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0  et RJ45  C - 50/60Hz  DC  5A
Network	WiFi + Bluetooth LAN Port Input Voltage Rated Voltage Rated Current	Ethernet Interfa  USB Socket HOST  WiFi (802.11b/g/n), Bluetooth V2.1  Etherne  100-240VA0  12V  1.5	ice (RJ45) - PoE  Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0  et RJ45  C - 50/60Hz  DC  SA  W
Network  Power Supply	WiFi + Bluetooth  LAN Port  Input Voltage  Rated Voltage  Rated Current  Rated Power  Certification	Ethernet Interfa  USB Socket HOST  WiFi (802.11b/g/n), Bluetooth V2.1  Etherne  100-240VA0  12V  1.5  FCC,cULus	ice (RJ45) - PoE  Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0  et RJ45  C - 50/60Hz  DC  SA  W  CE, FCC, CCC, CE, GS and cULus
Network	WiFi + Bluetooth  LAN Port  Input Voltage  Rated Voltage  Rated Current  Rated Power	Ethernet Interfa  USB Socket HOST  WiFi (802.11b/g/n), Bluetooth V2.1  Etherne  100-240VA0  12V  1.5	ice (RJ45) - PoE  Mode By Default  +EDR/BT v3.0/BT v3.0+HS/BT v4.0  et RJ45  C - 50/60Hz  DC  SA  W  CE, FCC, CCC, CE, GS and cULus



